

Ducati Hypermotard 2013-2018 Fender Eliminator Kit

Parts List

x1 License plate holder
x1 License plate belly pan
x1 License plate LED light
x1 License plate adapter harness
x4 6x12mm allen bolts
x4 6mm washers
x4 6mm nylon nuts
x4 8x12mm allen bolts
x4 8mm washers

x2 5x40mm allen bolts
x2 5mm washers
x2 OEM signal adapters + lock spacer
x2 Aftermarket 10mm signal adapters

1. Remove rear fender (4 bolts). You no longer need these bolts

2. Separate the factory fender in half and disconnect the rear turn signals and license plate light. This harness will be used later

3. Attach the LED license plate light to the plate holder and attach the adapter harness to the LED plate light. White>White and Black>Black

4. Attach the belly pan to the undertail using two 8x12mm allen bolts and washers into the 2 rear mounting holes. Do not tighten them at this point

5. Attach the license plate holder to the belly pan using the remaining two 8x12mm bolts and washers. Make sure to run the license plate light harness through the center hold first and plug it in. Tighten all four 8x12mm bolts.

6. Mount the license plate to the plate holder using the four 6x12mm bolts, washers, and lock nuts from this kit.

7. Optional: Mount the OEM or aftermarket turn signal adapters to the license plate mounting holes on the plate holder using two/four 6x12mm allen bolts, washers, and nuts. Install the OEM or aftermarket turn signals onto the adapter and route wires through center hole and plug into appropriate plug removed from step 2. Aftermarket signals may require wiring. Refer to illustration on right to mount factory signals. SX=Left, DX=Right

8. Check all lighting

