

2025-2026 Ducati Panigale/Streetfighter V4/V2 Fender Eliminator Kit - Low Profile (Tucked)

Part No. FE-D25PSF-LP

Parts List

x1 Plate Holder
x1 Cover Plate
x1 LED license plate light
x1 License plate light adapter harness
x2 M5x20mm bolts
x6 M5x12mm bolts
x8 M5 washer

x4 M6x14mm bolts
x4 M6 lock nuts
x4 M6 large OD washers
x1 Grommet (pre-installed)
x2 Plastic spacers 12x6x9mm for V2/V2S (ODxIDxH)
x2 Plastic spacers 12x6x10.5mm for V4/V4S (ODxIDxH)

Required

3mm allen tool
4mm allen tool
7mm socket or wrench
10mm socket or wrench
Medium strength thread locker (Blue Loctite, etc)

1. Factory rear fender assembly removal - 4 bolts from underneath using 4mm allen, support fender on last bolt.
2. While supporting fender, unplug left signal, right signal, and license plate light.
3. Fender eliminator kit comes pre-assembled for shipping, separate the plate holder from the cover plate by removing the four (4) M5x12mm bolts, 2 from each side.
4. Mount the LED license plate light to the plate holder by feeding the wires through the center hole one at a time and securing with the 2 nuts using 7mm socket, ensure the LEDs are facing down towards the license plate.
5. Prepare the cover plate - peel and stick two (2) plastic spacers on top of the 2 forward holes on the cover plate, see illustration. For V4/V4S, use the 12x6x10.5 spacers (the taller ones). For V2/V2S, use the 12x6x9mm spacers (the shorter ones). Make sure to align the holes.
6. Grab the license plate adapter harness from this kit and plug the plastic connector end into the bike (same connector removed from step 2 above).
7. Prepare (2) M5x12mm bolts and two (2) M5x20mm bolts along with M5 washers on each. Place with a drop of medium strength Loctite (blue) or thread locker on each bolt and a 3mm allen tool within close proximity.
8. Feed the other end of the adapter harness top down through the grommet on the cover plate, pull through 2-3 inches of wire harness. While feeding the excess wires into the cavity space in the under tail, place the cover plate to the under tail using a pivoting motion so that the forward edge of the cover plate wedges into the slot on the plastic under tail, then secure using two (2) M5x12mm bolts on the rearward 2 holes and two (2) M5x20mm bolts in the forward 2 holes (the forward holes are the ones with the spacers)..
9. Mounting the plate holder assembly. Prepare four (4) M5x12mm bolts from this kit along with M5 washers on each bolt and place a drop of medium strength Loctite (blue) or thread locker on each. Keep these within reachable close vicinity and a 3mm allen tool. While plugging in the license plate light (yellow>white and blue>black) mount the plate holder to the cover plate using four (4) M5x12mm bolts, two per side - see illustration.
10. Mount the license plate to the plate holder using four (4) M6x14 bolts, M6 large OD washers and M6 lock nuts (Bolt>Plate>Plate Holder>Washer>Nut)

2 plastic spacers (peel and stick onto cover plate)
For V4/V4S, use 12x6x10.5 (taller ones)
For V2/V2S, use 12x6x9 (shorter ones)

