

# 2017-2019, 2020-2023 Kawasaki Z900/ZH2 Fender Eliminator Kit Low Profile

Part No. FE-K17Z900-LP, FE-K20Z900-LP

## Parts List

x1 Plate holder	x8 M6 nylon lock nuts
x1 Cover plate	x4 M6 washers
x1 License plate LED light	x4 M6 large OD washers
x1 License plate harness adapter	x4 Plastic spacers
x4 M6x25mm bolts	
x4 M6x14mm bolts	

1. Remove passenger seat. Reach in trunk and pull back the silver 'U' handle to release driver seat, pull driver seat upwards

2. Remove the plastic upper tail section (4 bolts at the rear and 2 screws up front) and carefully slide up and rearwards to release from locking tabs

3. Locate the black plastic boot on the right side of the bike and slide it back, unplug the left/right turn signals (black and gray plugs) and the license plate light (black plug)

4. Remove the rear fender (1 screw and 4 bolts from top) before removing the last bolt support the fender so it does not drop down, carefully drop fender down and pull out the 3 wires with it.

5. Peel and stick the 4 plastic spacers to the backside of the cover plate. Make sure the wire feed cover section of the cover plate is facing right of the bike.

6. Loosely mount the cover plate to the bike's under tail using two M6x25mm bolts, M6 washers and M6 lock nuts in the 2 rearward holes, so that access to the wire feed path is still accessible.

7. Attach LED license plate light to the plate holder running the wire through the center hole and secure with the 2 nuts. Connect the license plate light adapter harness to the LED light in the following configuration:

**2017-2019 models: white>white and black>black**

**2020+ models: white>black and black>white**

8. While feeding the license plate wire/adaptor up through the feed path to the under tail, mount the plate holder to the cover plate to the under tail using remaining two M6x25mm bolts, M6 washers and M6 lock nuts. See illustration

9. Pull up any wire slack up from the trunk area and plug the license plate light back into the bike. Tighten the 2 bolts from step 6 above.

10. Reinstall the plastic upper tail section and reinstall seat

11. Mount the license plate using the four M6x14mm bolts, M6 large OD washers and M6 lock nuts

12. Check all lights for functionality before going on a road test

