

2016-2017 Suzuki GSX-S1000/F Fender Eliminator Kit

Parts List

x1 License plate holder
 x1 Cover plate
 x1 License plate LED light
 x1 License plate harness adapter
 x4 M6x30mm bolts
 x4 M6x16mm bolts
 x4 M6 nylon lock nuts
 x4 M6 washers
 x4 M6 large OD washers
 x4 Plastic spacers
 x2 Factory signal adapters (For USA/Similar models)
 x2 Aftermarket signal adapters

Recommended

Loctite or Threadsealer

1. Remove the passenger seat. Remove rider seat (1 bolt) slide up and back
2. Locate the 3 wire looms for the left/right turn signals and the license plate light on the right side of the bike. Undo the 2 cable ties to free the looms from the chassis and unplug signals (gray/black plugs) and license plate (white plug). Undo the last cable tie holding the harness to the chassis and pull out the wire looms.
3. Remove the rear fender (4 bolts from underneath) support fender before removing last bolt and guide the 3 wires looms out with it. These bolts are no longer needed.

OPTIONAL: Mount turn signals

4. Attach LED license plate light to the plate holder running the wire through the center hole. Connect the license plate light adapter harness to the LED light red>white and black>black, then run through oval hole on cover plate.
5. Run the wires through the rearward rectangular hole on the undertail and mount the plate holder to the cover plate to chassis using the 4 (four) M6x30mm bolts, washers and plastic spacers. Apply a drop of loctite or threadsealer on these bolts. See illustration
6. Plug the license plate light and optional turn signal wires back into the bike securing with cable ties removed from step 2 above.
7. Mount the license plate to the plate holder using the 4 (four) M6x16mm bolts, large OD washers, and lock nuts
8. Check all lights for functionality before going on a road test

Mounting factory turn signals:

1. Remove the license plate mount off the fender
2. Separate the fender in half (5 screws)
3. Cut the cable tie securing the wires and unbolt the turn signal (1 nut) then pull out the turn signals
4. Remount the turn signals onto the factory turn signal adapters included in this kit
5. Mount the adapter behind the plate holder using the same bolts to mount the license plate

Mounting aftermarket turn signals:

1. Mount the 2 aftermarket turn signal adapters to the fender eliminator assembly plate mount upper hole.
2. Mount the aftermarket 10mm hole mount turn signals.
3. Run the wires through the rearward square hole and wire it to the bike.

