

Triumph Speed Triple 2011-2015 Fender Eliminator Kit

Parts List

x1 License plate holder
x1 License plate LED light
x1 License plate adapter harness
x6 M6x14mm allen bolts
x2 M6 washers
x4 M6 large OD washers
x6 M6 nylon lock nuts

Required

Loctite or thread sealer

1. Remove the center under plastic undertail cover (2 plastic rivets and 1 bolt in the center) then slide back and down to remove
2. Disconnect license plate wire and left and right turn signal wires
3. Remove the rear fender (4 bolts from underneath) and carefully drop it down.
4. Grab the fender and remove the center nut clip and transfer it over to the new plate holder

Optional: Install turn signals - See below

5. Mount the LED license plate license plate light to the plate holder and connect the license plate light adapter harness (Black>Black and White>white)
6. While plugging back in the license plate light (and optional turn signal connectors), mount the plate holder to the chassis using the 4 bolts from step 3 above. Apply a drop of loctite or thread sealer on these bolts. See illustration

7. Re-install the center under plastic undertail cover

8. Mount the license plate to the plate holder using 4 M6x14mm bolts, M6 large OD washers and M6 lock nuts.

Mounting OEM turn signals:

Grab the rear fender and remove the turn signal (1 bolt). Mount the turn signal to the 2 circular holes on the support gusset of the plate holder using the M6x14mm bolts, M6 washer, and M6 lock nut from this kit. See illustration

Mounting aftermarket in-hole turn signal:

Mount the turn signal in the either of the 3 holes on the support gusset of the plate holder depending on preference and clearance of the muffler.

