

2015+ Yamaha R1/R1M/R1S

Fender Eliminator Kit

Parts List

- x1 License plate holder
- x1 Cover plate
- x1 License plate LED light
- x1 License plate light harness adapter
- x3 M6x30mm bolts
- x4 M6x16mm bolts
- x7 M6 nylon lock nuts
- x3 M6 washers (spare)
- x4 M6 large OD washers
- x2 Factory signal adapters
- x2 Aftermarket signal adapters

1. Remove passenger seat. Remove driver seat (2 bolts underneath rear cushion area). Remove the center black plastic panel between seats (4 plastic screw/rivets).

2. Unplug the left and right turn signals (black and white large connector) and license plate light plug (small white connector). Undo the wire tie and unclip left and right turn signal harness from the body. TIP: unplug the tail light harness to make routing easier, make sure to plug it back once done.

3. Unbolt the 3 bolts holding the fender to the chassis from above, support fender from underneath. Remove fender and turn signal/license plate wires with it.

Optional: mount turn signals, see below

4. Mount the LED plate light to the license plate holder and run the wire through the open slot up top.

5. Mount the license plate holder and cover plate to the chassis using the three M6x30mm bolts and lock nuts alongside the factory special washer. If factory special washer is no longer present, use the three spare M6 washers. See illustration to right.

6. Connect the license plate light harness adapter (Blue>White and Yellow>Black) to the LED plate light and connect it back to the bikes harness (small white plug).

7. Mount the license plate using the four M6x16mm bolts, large OD washers, and lock nuts. Bolt>Plate>License plate holder>washer>nut

Installing with factory rear turn signals

1. Remove the factory turn signals off the factory rear fender. Remove the under cover to access the locking spacers, remove then pop off the signals. Mount the factory turn signals to the factory turn signal adapter in the reverse steps from removal process..
Black plug=Left, White plug=Right

2. Mount the entire assembly behind the license plate holder using same holes for the license plate

3. Route the wires through the rear slot and plug it back into the left and right turn signal plugs

Installing with aftermarket 10mm hole mount turn signals

1. Mount the 2 aftermarket turn signal adapters to the license plate holder upper hole.

2. Mount the aftermarket 10mm hole mount turn signals to adapter

3. Run the wires through the elongated slot and wire it to the bike

