

Yamaha R6 2003-2005, R6S 2006-2009, R1 2002-2003 Fender Eliminator Kit

Parts List

x1 License plate holder
x1 X-Ring Spacer
x1 License plate LED light
x1 License plate adapter harness
x4 6x12mm allen bolts
x4 6x25mm allen bolts
x4 6mm washers
x4 6mm Large OD washers
x8 6mm nylon lock nuts
x2 OEM signal adapters
x2 Aftermarket 10mm signal adapters

1. Remove rear seat and unbolt rear OE fender (4 screws). These screws will no longer be used. Drop the rear fender down.

2. Unplug left and right turn signal connectors as well as license plate light connector. Under tail may need to be removed in order to access these connectors.

3. Mount license plate holder to the bike using the X-Ring Spacer, four M6x25 bolts, large OD washers and lock nuts supplied in this kit. See illustration to right.

4. Attach the LED license plate light to plate holder. Feed wires through hole on plate holder. Attach adapter harness to LED plate light (Red>White wire and Black>Black wire) and plug it back into bike removed from step 2.

5. Mount license plate to plate holder using four 6x12mm bolts, washers, and lock nuts from this kit.

6. Optional: Mount OEM or aftermarket turn signal adapters to license plate mounting holes on plate holder using two/four 6x12mm allen bolts, washers, and nuts. Install OEM or aftermarket turn signals onto adapter and route wires through rear hole of the fender hole block plate and plug into appropriate plug removed from step 2. Aftermarket signals may require wiring. Refer to illustration on right to mount factory signals.

8. Check all lighting

