

Kawasaki Ninja ZX-10R 2011-2014

Rear Panel Sequential LED Turn Signals Installation Guide

Part# K-12ZX10-C/S

Parts List

- x1 Left hand signal lamp
- x1 Right hand signal lamp
- x2 Plug and play resistor harness
- x4 M5x22 button head socket screws
- x2 M6x16 flat washers
- x4 M13x24 spacers
- x4 M5 nylon lock nuts (for international models)

For USA and similar model ZX-10R

Exchange the factory screws with the included longer M5x22 screws. Reuse factory lock nuts.

For International model ZX-10R

Remove and discard the 4 rubber dampers, collars, and swell nuts and use the included M5 nylon lock nuts

Installation tip

Align the signal lamps to the tail light and lower under cover first before tightening

Connecting the turn signals

Connect the resistor harness to the turn signal lamps. Blue/Blue, Yellow/Yellow, and Blacks/Blacks. Connect the other end to the bikes factory turn signal plugs as follows:

- Yellow/Black - Grey plug (right signal)
- Blue/Black - Black plug (left signal)

Programming instructions

These signals lamps feature a configurable signal pattern. Choose from sequential or standard. We recommend to program the signals before installation because it requires constant power. Make a pair of jumper cables and power up the signals directly from the battery or 12V power supply.

Locate and remove the small rubber plug on the back housing. Underneath is a small button. Use a small pin or other tool and press the button twice within 1 second of each other. The signal pattern has now been changed. The sequential pattern is defaulted right out of the box.

