

TLCR-001-C/S Specifications

Width	133mm (5.24")
Height	30mm (1.18")
Depth	43.8mm (1.72")
Mounting Bolt Length	15mm (6.06")
Bolt	M6x1.0 (nut/washer included)
Harness Length	250mm (9.84")
Connector Type	Male bullet 4mm
Resistor Specs	10W 7.5 Ohm (x2)
Max Material Mount Thickness	5mm
Red Wire	Running Light (+)
White Wire	Brake Light (+)
Blue Wire	Left Signal (+)
Yellow Wire	Right Signal (+)
Green Wire	License Plate Light (+)
Black Wire	Ground (-)

Programming Instructions

NOTE: It is recommended that the tail light is programmed prior to installation if the button cannot be reached after it is mounted to the bike. Simply connect the main harness to supply power to the tail light while the key is in the "ON" position.

1. Locate the 4mm round rubber plug on back housing and remove it
2. Turn the key to the "ON" position, making sure the park lights are on
3. Beneath the rubber plug is a push button, use a pin or similar tool to press the button consecutively within 1 second between each press to program the following:

ON/OFF Stop Alert - hit button 3 times
 ON/OFF Sequential Signals - hit button 4 times

The parking light (red) will flash off and on again within 2 seconds to verify the settings have been saved. The factory settings are defaulted to ON right out of the box for all functions.

4. Install the rubber plug back into the hole

Note: Turning off Stop Alert will enable the brake light to be constant on during brake activation just like stock. Turning off sequential signals will enable the entire left or right half to turn on when the signals are activated.

